

Mac PlantMaster Electric



	11lt per minute	13lt per minute	13lt per minute	13lt
Water Flow per minute	11lt per minute	13lt per minute	13lt per minute	13lt
Pressure	120bar	170bar	170bar	170bar
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp,
Heating Power	18kW	24Kw	36Kw	48Kw
Shutdown System	Timed total stop	Timed total stop	Timed total stop	Timed total
Max Temperature	80°C	80°C	80°C	80°C
Volts Amps Watts	415v / 32A / 22Kw	415v / 45A / 29.5Kw	415v / 60A / 41.5Kw	415v /
Weight	250kg	250kg	250kg	250kg
Dimensions (h x w x d)	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm

STANDARD FEATURES

- Low revving 1450rpm pump & motor
- High pressure interpump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Low thermal loss in standby
- Maximum temperature output 80°C
- Digital temperature display
- Simple 24v controls
- Available from 18kW to 48kW

CABINET FINISH

- Available in powder coated or stainless steel

OPTIONAL ACCESSORIES

- Remote control box
- Coin / token acceptor
- Lance & lance holder
- Key fob system