

Mack Avant GRP



Water Flow	12lt per minute	15lt per minute	9lt per minute
Pressure	100bar, 1500psi	200bar, 3000psi	100bar, 1500psi
Motor Specification	3hp, 1450rpm	7.5hp, 1450rpm	3hp, 1450rpm
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-150°C	0-150°C	0-150°C
Power	240v	415v	110v
Weight	110kg	120kg	100kg
Dimensions (h x w x d)	85 x 63 x 100cm	85 x 63 x 100cm	85 x 63 x 100cm

STANDARD FEATURES

- Heavy-duty steel chassis
- Heavy duty GRP plastic cover
- 4 large robust wheels for tough terrain
- Efficient M2 boiler system & double spiral coil
- High pressure chemical system
- Steam stage with low pressure steam valve
- ST66 chemical valve for improved calibration
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric motor
- Automatic stop/start system
- Bypass valve and safety valve
- Pressure gauge
- Burner control with flow switch and thermostat
- 24v low tension safety controls
- Large 31ltr easy fill fuel tank with low level sensor
- Low level fuel warning lamp with burner shut down
- Mains power on lamp
- Including 10mt high pressure hose, single lance and heavy duty trigger

OPTIONAL ACCESSORIES

- Stainless steel manual hose reel
- Stainless steel lance holder
- Frost protection with heater tube
- Flame failure and leak detection system
- Timed chemical systems
- Remote control options
- Stainless steel break water tank
- Hour counter

